

Serial No. 09/214,022
Art Unit 1772

Amendment B

cf
cut
corresponding crease line[s] of the packaging laminate, the plurality of linear fold regions having a bond strength less [that] than the first bond strength, wherein when the laminate is folded at the crease lines, the first and second layers are separable from one another.

Please cancel claim 18. ✓

Please amend claim 19 as follows:

Sub 02
19. (Twice Amended) A method for producing a crease-lined packaging laminate, the method comprising:

providing a first layer of the packaging laminate, the first layer having a first plurality of linear fold regions and a first plurality of non-folding regions;

C2
providing a second layer of the packaging laminate, the second layer having a second plurality of linear fold regions corresponding to the first plurality of linear fold regions and a second plurality of non-folding regions corresponding to the first plurality of non-folding regions, the second layer being coextensive with the first layer; and

bonding the first layer to the second layer wherein the first layer first plurality of non-folded regions is bonded to the second layer second plurality of non-folded bonded regions [as] at a first bond strength, [and] wherein the first layer first plurality of linear fold regions is bonded to the second layer second plurality of linear fold regions at a bond[s] strength less than the first bond strength, and wherein when the laminate is folded at the linear fold regions, the first and second layers are separable from one another.

C3
[Please amend claim 27 as follows:]

27. (Twice Amended) A packaging container having non-scored crease lines, the packaging container comprising:

a first layer having a first plurality of linear fold regions, each linear fold region defining a [plurality] corresponding crease line[s] of the packaging container, the first layer also having a